



深圳德彩光电有限公司
Shenzhen Dicolor Optoelectronics Co.,Ltd

LED模组规格书

LED MODULE SPECIFICATION

编号 (NO.) :	DI-P10F4
类型 (Type) :	Indoor LED Module
间距 (Pitch) :	10 mm
驱动 (Driving) :	Static Duty
版本 (Version) :	1.0



请避免重物挤压灯面!



小心静电损坏LED!



非专业人员请勿维修!

地址:深圳市宝安区福永镇福海大道福海科技工业园B3区2栋4楼

Address:Floor 4,Seat 2,B3 District,FuHai Technology Industry Park,Fuyong
Town,Shenzhen,China

电话(Tel):0086-755-29604770/29604771/29604749

传真(Fax):0086-755-29604042

网址(Web):[Http://www.dicolor.cn](http://www.dicolor.cn)

邮编(Post code):518103




深圳德彩光电有限公司

Shenzhen Dicolor Optoelectronics Co.,Ltd


DI-P10F4

户内模组 (INDOOR MODULE)

单位 / Unit : mm




FRONT VIEW




Pin Assignment (Data JP1/JP2 - F.C.16)

Pin NO.	Function	Pin NO.	Function
1	R0	2	G0
3	B0	4	R1
5	G1	6	B1
7	R2	8	G2
9	B2	10	R3
11	G3	12	B3
13	CLR	14	LAT
15	OE	16	GND



BACK VIEW



SIDE VIEW



DI-P10F4

户内模组 (INDOOR MODULE)

主要技术指标


MAIN SPECIFICATIONS

(温度条件 Ta = 25°C)

项目 (ITEM)	参数 DESCRIPTION
像素间距 (Pixel Pitch)	Pitch 10 mm
显示分辨率 (Display resolution)	16 x 16 Dots
像素基色 (Pixel configuration)	1 R, 1 G, 1 B
物理密度 (Physical density)	10000 (pixels / m ²)
驱动方式 (Driving Method)	Static Duty
外形尺寸 (Panel size)	159.8x159.8mm
灰度等级 (Gray scale)	256 greys for each colour (16,7 77,216 grade) 每种颜色,256级;共16,777,216级
显示亮度 (Brightness)	1800 ± 10% Nit
模组视角 (Viewing angle)	H:160° / V:120°
最佳视距 (Option distance)	> 8 M
LED封装 (LED Encapsulation)	SMD0805
LED波长 (LED Wavelength)	R:620~635nm G:515~530nm B:460~475nm
工作电压 (Working Voltage)	DC 5 V
使用功耗 (Working Consumption)	42 W
使用寿命 (Life Time)	100,000 Hours
环境温度 (Environment Temperature)	-20°C ~ 60°C

数据传输原理图

Drive Data Register Direction



FRONT VIEW (LAMP VIEW)